

MULTILIFT HOOKLIFT SYSTEM

12,000 - 72,000 LB CAPACITIES

NATIONWIDE
SERVICE &
SUPPORT



Structural Components



MULTILIFT

MODEL	CAPACITY (LB)	OPTIMUM BODY LENGTHS (FT)	MAX. TIPPING ANGLE [°]	HOOK HEIGHT (IN)	COMMON CA/CT (IN)	COMMON GVWR (LB)	FRAME HEIGHT (IN)	CLEAR FRAME (IN)	WEIGHT (LB)
XR5S-3050	12,000	10 - 12	50	36	84	19,500	UP TO 36	138	1,345
XR5S-3250	12,000	11 - 13	50	36	108	19,500	UP TO 36	149	1,433
XR5S-3650	12,000	12 - 14	50	36	120	19,500	UP TO 36	163	1,521
XR7S-3250	16,000	11 - 13	50	36	108	22,000	UP TO 40	149	2,050
XR7S-3650	16,000	12 - 14	50	36	120	22,000	UP TO 40	163	2,116
XR7S-4150	16,000	14 - 16	50	36	138	22,000	UP TO 40	179	2,183
XR8S-3650	18,000	12 - 14	50	36 / 54	120	26,000	UP TO 40	163	2,227
XR8S-4150	18,000	14 - 16	50	36 / 54	138	26,000	UP TO 40	181	2,293
XR10S-3650	22,000	12 - 14	50	54 / 62	128	33,000	UP TO 40	163	2,293
XR10S-4150	22,000	14 - 16	50	54 / 62	144	33,000	UP TO 40	181	2,359
XR10S-5100	22,000	17 - 19	50	54 / 62	174	33,000	UP TO 40	217	2,535
UTL14S-4300	30,000	14 - 16	50	54 / 62	156 / 138	35,000 / 42,000	UP TO 44	191	3,594
UTL14S-4600	30,000	15 - 17	50	54 / 62	168 / 145	35,000 / 42,000	UP TO 44	202	3,660
UTL14S-5600	30,000	18 - 20	50	54 / 62	204 / 186	35,000 / 42,000	UP TO 44	240	4,101
UTL16S-4600	40,000	15 - 17	50	54 / 62	145	48,000	UP TO 45	204	3,836
UTL16S-5600	40,000	18 - 20	50	54 / 62	186	48,000	UP TO 45	241	4,277
UTL21S-5600	50,000	18 - 20	50	54 / 62	186	58,000	UP TO 45	242	5,512
UTL21S-6100	50,000	20 - 22	50	54 / 62	204	58,000	UP TO 45	262	5,622
UTL26S-6100	60,000	20 - 22	50	54 / 62	204	68,000	UP TO 45	262	6,063
UTL26S-7000	60,000	23 - 25	50	62	230	68,000	UP TO 45	297	6,790
UTL30S-6100	72,000	20 - 22	50	62	204	80,000	UP TO 45	262	6,327

STANDARD PRODUCT FEATURES	XR5S-XR10S	ULT14S-ULT30S
Electric Cab Control	X	X
2-Speed Control		X
Flex PLC Control (up to 18 programmable buttons)		X
Body Up Indicator Light / Warning	X	X
High Tensile Steel Construction	X	X
Dual Pivot Design (true dump capability)	X	X
Hook Safety Latch	X	X
Soft Lowering (dump cycle)		X
Friction Relief (load/unload cycle)		X
Float Function (rough & off-road situations)		X
Pull Limiter (managing short bodies)		X
Solid Cast Inserts (at all critical high-stress areas)		X
Sensors & Wiring - IP67 rating (dust & water proof)	X	X
Paint - zinc primer and finish top coat (black - RAL 9005)	X	X
ISO 9001 Certification	X	X

MULTILIFT APPLICATIONS

- Dump bodies
- Flatbeds
- Liquid/water tanks
- Sand/salt spreaders
- Open-top containers
- Chipper bodies
- Leaf loaders
- Jet/vac
- Van bodies
- Asphalt patchers
- Cement mixers
- Mobile office
- and many more